



PRODUCT SPECIFICATION SHEET

Fuelstop TFV Capillary 1/2" Fire Valve

Part Number: FVC-xxxxxx-1

Product Description

A capillary fire valve is a **legal requirement for fuel burners**. Make sure you fit the best available by choosing Fuelstop TFV.

Unlike other fire valves, the **Fuelstop TFV** conforms to British safety standards and it is also more reliable, making the perfect choice for installers and customers. You want the best fire valve available - the one that guarantees more **safety, flexibility and reliability** with less hassle.

The Fuelstop has a **fluid filled capillary** and bellows means that it is more responsive (than other air filled capillary and bellows on the market). We can therefore set the trip mechanism with more tolerance (this does not have to be set on a hair trigger), which results in **zero nuisance tripping** and within a tighter trip range. In fact it is the only fire valve we know of that is approved to British Standard BS 799 part 5.



Features

- 3/8" & 1/2" BSP Female
- 1.5m - 35m Capillary length (depends on model)
- Temp Ranges: 66°C to 72°C and 86°C to 95°C
- Flow rate: 180 litres per hr /1.2m head
- Liquid filled capillary
- OFTEC Approved

72°C Fire Valves - 3/8" Connection

Part Number	Description
FVC-7201510	3/8" BSP (10mm Compression) 72°C Thermostatic Fire Valve - 1.5m
FVC-720310	3/8" BSP (10mm Compression) 72°C Thermostatic Fire Valve - 3m
FVC-720610	3/8" BSP (10mm Compression) 72°C Thermostatic Fire Valve - 6m
FVC-721010	3/8" BSP (10mm Compression) 72°C Thermostatic Fire Valve - 10m
FVC-721210	3/8" BSP (10mm Compression) 72°C Thermostatic Fire Valve - 12m
FVC-721510	3/8" BSP (10mm Compression) 72°C Thermostatic Fire Valve - 15m
FVC-722010	3/8" BSP (10mm Compression) 72°C Thermostatic Fire Valve - 20m
FVC-722510	3/8" BSP (10mm Compression) 72°C Thermostatic Fire Valve - 25m
FVC-723510	3/8" BSP (10mm Compression) 72°C Thermostatic Fire Valve - 35m

72°C Fire Valves - 1/2" Connection

FVC-7201512	1/2" BSP 72°C Thermostatic Fire Valve - 1.5m
FVC-720312	1/2" BSP 72°C Thermostatic Fire Valve - 3m
FVC-720612	1/2" BSP 72°C Thermostatic Fire Valve - 6m
FVC-721012	1/2" BSP 72°C Thermostatic Fire Valve - 10m
FVC-721212	1/2" BSP 72°C Thermostatic Fire Valve - 12m
FVC-721510	1/2" BSP 72°C Thermostatic Fire Valve - 15m
FVC-722010	1/2" BSP 72°C Thermostatic Fire Valve - 20m
FVC-722510	1/2" BSP 72°C Thermostatic Fire Valve - 25m
FVC-723510	1/2" BSP 72°C Thermostatic Fire Valve - 35m

95°C Fire Valves - 3/8" Connection

Part Number	Description
FVC-950210	3/8" BSP (10mm Compression) 95°C Thermostatic Fire Valve - 2m
FVC-950310	3/8" BSP (10mm Compression) 95°C Thermostatic Fire Valve - 3m
FVC-950610	3/8" BSP (10mm Compression) 95°C Thermostatic Fire Valve - 6m
FVC-951010	3/8" BSP (10mm Compression) 95°C Thermostatic Fire Valve - 10m
FVC-951210	3/8" BSP (10mm Compression) 95°C Thermostatic Fire Valve - 12m
FVC-951510	3/8" BSP (10mm Compression) 95°C Thermostatic Fire Valve - 15m
FVC-952010	3/8" BSP (10mm Compression) 95°C Thermostatic Fire Valve - 20m
FVC-952510	3/8" BSP (10mm Compression) 95°C Thermostatic Fire Valve - 25m
FVC-953510	3/8" BSP (10mm Compression) 95°C Thermostatic Fire Valve - 35m

95°C Fire Valves - 1/2" Connection

FVC-9501512	1/2" BSP 95°C Thermostatic Fire Valve - 1.5m
FVC-950312	1/2" BSP 95°C Thermostatic Fire Valve - 3m
FVC-950612	1/2" BSP 95°C Thermostatic Fire Valve - 6m
FVC-951012	1/2" BSP 95°C Thermostatic Fire Valve - 10m
FVC-951212	1/2" BSP 95°C Thermostatic Fire Valve - 12m
FVC-951510	1/2" BSP 95°C Thermostatic Fire Valve - 15m
FVC-952010	1/2" BSP 95°C Thermostatic Fire Valve - 20m
FVC-952510	1/2" BSP 95°C Thermostatic Fire Valve - 25m
FVC-953510	1/2" BSP 95°C Thermostatic Fire Valve - 35m

Accessories

Part Number	Description
FV30-032/033	Fire Valve Support Bracket & Phial Clip



Certificate Number – 1303
ISO 9001:2015

NEED MORE INFORMATION?

○ 01373 822220

○ sales@fueldump.co.uk

○ www.fueldump.co.uk