REFUELLING & LIQUID TRANSFER / FUEL DELIVERY NOZZLES



PRODUCT SPECIFICATION SHEET Piusi Self 3000 Manual Fuel Nozzle





Nozzle

Flow Rate:

150lpm

Product Description

The Piusi Self 3000 is a manual fuel nozzle designed for the dispensing of diesel and oil at high flow rates and pressure conditions. This oil and diesel nozzle is a cost effective solution suitable for any type of pumping system that operates with 150 litres per minute.

Manufactured with a resistant aluminium body enclosed in a anti-shock plastic shell that increases the nozzle's ease of handling by making the grip comfortable even when used at low temperatures.

Features

- O Manual Fuel Nozzle
- O Plastic anti-shock handle protector
- O Suitable for diesel and oil

- O Die cast aluminium body
- O Maximum flow rate: 150lpm
- O Supplied with 1" F BSP swivel

Part Number	Description	Specifications
P8-650000	Piusi Self 3000 Oil and Diesel Nozzle	 Max Flow Rate (lpm) - 150 Max Pressure (Bar) - 10 Spout OD (mm) - 20 Body material - Aluminium Alloy Seal material - HNBR Inlet - 1" F BSPP Swivel Manual Diesel and Oil
P8-65001A	Piusi Self 3000 Oil and Diesel Nozzle - Unleaded	 Max Flow Rate (lpm) - 150 Max Pressure (Bar) - 10 Spout OD (mm) - 20 Body material - Aluminium Alloy Seal material - HNBR Inlet - 1" F BSPP Swivel Manual Diesel and Oil
P8-65003A	Piusi Self 3000 ATEX Fuel Nozzle	 Max Flow Rate (lpm) - 150 Max Pressure (Bar) - 10 Spout OD (mm) - 20 Body material - Aluminium Alloy Seal material - HNBR Inlet - 1" F BSPP Swivel Manual Diesel, Petrol and Kersosene

NEED MORE INFORMATION?

○ sales@fueldump.co.uk