

SPECIFICATION SHEET

TIGERLOOP PLUS

CONTACT:

01373 822220 sales@fueldump.co.uk

DESCRIPTION

In an oil heating system using a Tigerloop Plus, all oil passes through the automatic oil de-aerator, which effectively removes all gas/air bubbles from the system. This eliminates oil pump and nozzle problems associated with gas/air in the oil.

The Tigerloop Plus has been developed to meet the highest demands for cleaner air-free oil. The flagship of the Tigerloop range, the smart, all-in-one design includes a vacuum gauge for full control and simple troubleshooting, a shut off valve for easy service and a Spin-on paper filter for the toughest filtration needs. This unit has an extremely large filtration area of 1850 cm2 with a filtration grade of 20 microns.

FEATURES

- · Automatic de-aerator for oil burner
- Maximum operating temperature of 60°c
- Comes complete with filter bowl and filter element
- · Suitable for oil and kerosene
- · 3/8" F BSP Inlet/Outlet
- · Comes complete with wall bracket in box



PART NUMBER	DESCRIPTION	SPECIFICATIONS	PRICE
TL61101-P	Tigerloop Plus Deaerator	 Nozzle Capacity (I/h) - 110 Oil Flow (I/h) - 230 De-aerating capacity (I/h) - 8 Max operating temp - 60°c Max/Min Pressure - +0.5/-0.6 Pump Connection - 1/4" F Outlet Connerction - 1/4" F BSP Filtration Grade - 20 micron 	£393.85

ACCESSORIES & SPARES

PART NUMBER	DESCRIPTION	SPECIFICATIONS	PRICE
TL6050	Fitting kit for Tigerloop Original (External Installation)	 x2 Steel Braided Flexi Oil Lines (1m) Isolation Valve Compression Fittings Nuts & Olives Copper Pipe Inserts 	£30.64
TL61101-PF	Spare 20 Micron Filter		£11.07