



## SPECIFICATION SHEET

TIGERLOOP BIO

### CONTACT:

01373 822220

sales@fueldump.co.uk

## DESCRIPTION

The TigerLoop® De-aerator effectively removes all gas/air bubbles from the oil system, helping to eliminate any oil pump and nozzle problems associated with gas/air in the oil.

The TigerLoop® oil de-aerator preheats the oil by absorbing heat from the boiler room and friction heat from the oil pump, which reduces the problems associated with cold oil, gives cleaner combustion and enables reduced oil consumption.

A de-aerator with all the benefits of a Tigerloop Original that can be fitted internally.

With the addition of a simple to it 10mm vent pipe the removed air can be vented safely to the outside, ensuring only pure oil is passed through to the burner.

Compatible with Bio Oil and Mineral Oil



## FEATURES

- Automatic de-aerator for oil burner
- Suitable for oil and kerosene & Biofuel
- Maximum operating temperature of 60°C
- 1/4" F BSP Inlet/Outlet

PART NUMBER	DESCRIPTION	SPECIFICATIONS	PRICE
TL7000	Tigerloop Bio Deaerator	<ul style="list-style-type: none"> <li>• Nozzle Capacity (l/h) - 110</li> <li>• Oil Flow (l/h) - 230</li> <li>• Max return oil (l/h) - 120</li> <li>• De-aerating capacity (l/h) - 8</li> <li>• Max operating temp - 60°C</li> <li>• Max/Min Pressure - +0.5/-0.6</li> <li>• Inlet/Outlet - 1/4" F BSP</li> <li>• Kerosene, oil and biofuel</li> </ul>	£46.34

## ACCESSORIES & SPARES

PART NUMBER	DESCRIPTION	SPECIFICATIONS	PRICE
TL6051	Fitting kit for Tigerloop Original (Internal Installation)	<ul style="list-style-type: none"> <li>• x2 Steel Braided Flexi Oil Lines (1m)</li> <li>• Isolation Valve</li> <li>• Compression Fittings</li> <li>• Nuts &amp; Olives</li> <li>• Copper Pipe Inserts</li> </ul>	£30.64

## NEED MORE INFO?

Visit us on [www.fueldump.co.uk](http://www.fueldump.co.uk)