

SPECIFICATION SHEET

ZVA SLIMLINE 2 FUEL NOZZLE (ATEX APPROVED)

CONTACT

BRAND

01373 822220 sales@fueldump.co.uk

zVA

DESCRIPTION

This heavy duty ZVA Slimline 2 Automatic Nozzle is designed to shut off when the fuel tank is full and prevents overspill, due to it's high quality this nozzle is approved for refuelling in resale pumping applications and also flammable environments.

Due to their slimline spout, these diesel and petrol nozzles are ideal for both domestic and commercial vehicle refuelling at a maximum flow rate of 55 litres per minute. This is also supplied with a trigger guard for safety and robustness.

ZVA are well known brand of nozzles used in commercial forecourts, recognised for their durability and ease of use.



- Automatic fuel nozzle
- Maximum flow rate: 80ltr Per Min.
- Supplied with ¾" or 1" F BSP Swivel

- Suitable for diesel and petrol
- ATEX, EN13012 and TUV-SUD approved
- For pumping systems only

PART NUMBER	DESCRIPTION	SPECIFICATIONS	PRICE (EX. VAT)
P8-PF5001	ZVA Slimline 2 Fuel Pump Nozzle - 3/4"	 Max Flow Rate (lpm) - 80 Max Pressure (Bar) - 3.5 Spout OD (mm) - 25 Inlet - 3/4" F BSPP Swivel Automatic Diesel and Petrol 	£255.50
P8-PF5017	ZVA Slimline 2 Fuel Pump Nozzle - 1"	 Max Flow Rate (lpm) - 80 Max Pressure (Bar) - 3.5 Spout OD (mm) - 25 Inlet - 1" F BSPP Swivel Automatic Diesel and Petrol 	£255.50