

Diesel pump 60 l/min

110 V-1~AC-50 Hz



Item number: 23 054
EAN: 4048358230546

Technical data

Connecting cable, length (m):	1,8
Connection suction side:	G 1" female
Connection discharge side:	G 1" female
Hydraulic data	
Pump design:	vane pump, selfpriming
Delivery rate under free discharge (l/min):	60
Discharge pressure up to (bar):	1,8
Pumping media:	fuel oil and diesel
Motor data	
Voltage (V):	110
Frequency (Hz):	50
Thermal protection:	self resetting
Duty cycle (min):	Continuous operation – a real endurance runner
Type of construction:	IMB 3
Safety class:	IP54
Materials of parts in contact with liquid	
Seals:	FKM (Viton®)
Pump housing:	AlSi 12 (sea water resistant)
Rotor:	sintered metal
Vane:	POM
Dimensions LxWxH (mm):	280 x 115 x 170
Weight (kg):	6,3

Specification

- Vane pump, with integral bypass
- On/Off switch
- Siphon protection acc. to WHG (German government regulation for environmental care), continuously active
- Installation of flowmeter NUMERlxx³, three digits, is possible (23 192)

Special notes

- Small tolerances provide a high suction- and pressure performance
- The material composition of the vane-stator (runner ring) guarantees form-stability of the vanes up to 200°C
- Materials guarantee a low weight and an exceptional lifetime with optimized efficiency

Packaging

Dimensions LxWxH (mm):	370 x 225 x 200
Weight including package (kg):	6,9
Packing unit:	1,0