



PREMxx 35 l/min-9.2 gpm

12 V-DC-ABK-ZVPP-4 m

Item number: 23 711
EAN: 4103810237119

Technical data

Connecting cable with battery terminal clips, length (m) / (ft): 2 / 6.6
 Connection container: G 2" male, drum adapter
 Connection suction side: hose fitting DN 19
 Connection discharge side: G 1" male
Hydraulic data
 Pump design: axial gear
 Delivery rate under free discharge up to (l/min) / (gpm): 35 / 9.2
 Suction height up to (m) / (ft): 2,5 / 8.2
 Discharge height max. (m) / (ft): 15 / 49.2
 Pumping media: fuel oil and diesel
Motor data
 Voltage (V): 12 V DC
 Power consumption (A): 14
 Power (W): 180
 Thermal protection: self resetting
 Duty cycle (min): 30
 Rotation speed at 0,5 bar counterpressure (rpm): 7500
 Type of construction: IMB 5
 Safety class: IP34
 Material of pump housing and pump: PA 6
 Dimensions of pump LxWxH (mm) / (inch): 130 x 130 x 350 / 5.1 x 5.1 x 13.7
 Weight with accessories (kg) / (lb): 4,5 / 9.9

Specification

- For 200 up to 1000 l container
- Axial wheel pump with manual pump assembly (23 710)
- Illuminated on/off switch
- Motor with thermal protection switch, self resetting
- Siphon protection acc. to WHG (German government regulation for environmental care), continuously active
- Discharge hose, 4 m / 13,1 ft, DN 19, G 1" male, G 1" female (23 144 100)
- Polypropylene nozzle valve, ZVPP (23 161)
- Suction hose, 1,6 m / 5,2 ft, with brass strainer
- Barrel screw coupling, G 2" male
- Valuable sales package

Special notes

- The pump is lightweight and very quiet in operation.
- Resistant against small dirt particles in the liquid to be discharged
- The liquid column is to be established via manual pumping
- Can be manually operated in case of electric power blackout
- Pump can only be utilized as barrel pump
- Replace the carbons when the pump has delivered a volume of 100,000 l

Packaging

Dimensions LxWxH (mm) / (inch): 400 x 400 x 220 / 15.7 x 15.7 x 8.7
 Weight including package (kg) / (lb): 5,31 / 11.7
 Packing unit: 1,0