


PREMAxx 48 l/min

230 V-1~AC-50 Hz-GBS-ZVPP-4 m

Item number: 23 731 932
EAN: 4103810428500

Technical data

Connecting cable with GB-plug, length (m): 2
 Connection container: G 2" male, drum adapter
 Connection suction side: hose fitting DN 19
 Connection discharge side: G 1" male
Hydraulic data
 Pump design: axial gear
 Delivery rate under free discharge (l/min): 48
 Suction height (m): 2,5
 Discharge height max. (m): 15
 Flow media: fuel oil and diesel
Motor data
 Voltage (V): 230
 Frequency (Hz): 50
 Power consumption (A): 2,0
 Power (kW): 0,42
 Thermal protection: self resetting
 Duty cycle (min): 30
 Rotation speed at 0,5 bar counterpressure (rpm): 10000
 Type of construction: IMB 5
 Safety class: IP34
 Material of pump housing and pump: PA 6
 Dimensions of pump LxWxH (mm): 130 x 130 x 350
 Weight of motor and pump (kg): 2,5
 Weight with accessories (kg): 5,04

Specification

- For 200 up to 1000 l container
- Axial wheel pump with manual pump assembly (23 730 932)
- GB-plug, 2 m cable
- Illuminated on/off switch
- Motor with thermal protection switch, self resetting
- Siphon protection acc. to WHG (German government regulation for environmental care), continuously active
- Discharge hose, 4 m, DN 19, G 1" male, G 1" female
- Polypropylene nozzle valve, ZVPP (23 161)
- Suction hose, 1,6 m, with filter
- Barrel screw coupling, G 2" male
- Valuable sales package

Special notes

- The pump is lightweight and very quiet in operation.
- Resistant against small dirt particles in the liquid to be discharged
- The liquid column is to be established via manual pumping
- Can be manually operated in case of electric power blackout

Packaging

Dimensions LxWxH (mm): 400 x 400 x 220
 Weight including package (kg): 5,04
 Packing unit: 1,0