



SPECIFICATION SHEET

WATER TRAP FILTER

CONTACT:

01373 822220

sales@fueldump.co.uk

DESCRIPTION

A filter that allows you to easily drain off any water collected from your heating oil.

GENERAL INFORMATION

- Cover in die-cast aluminium holes for bracket's fitting (optional)
- Regenerated filtering element with pleated stainless steel wire. Transparent bowl made of Durethan Bayer resistant to the shocks.
- Upper plug for air bleeding.
- Practical plug for water and impurities draining from the bottom of the bowl.



OPERATION

The filtering action is articulated in three phases:

1. Separation: The incoming diesel oil changes speed and direction. The contaminated liquid and solid particles separate out and settle on the bottom of the tank from which they are drained before coming into contact with the filter element.

2. Coalescence: The suspended water particles come together and separate out from the diesel oil in the final part of the feed pipe.

3. Filtration: The purified diesel oil crosses the stainless steel filter element. This deals with any micronic particles still suspended after the separation treatment phases 1 and 2.



PART NUMBER	DESCRIPTION	SPECIFICATIONS	PRICE
GFH3578-W-3/8	Water Trap Filter for Heating Oil	<ul style="list-style-type: none"> • Connection - 3/8" BSP • Filtering Degree - 60-100um • Max Working Pressure - 2 Bar • Max Operating Temp - 50°C • Dimensions: 80mm across x 136mm down 	£68.23

ACCESSORIES & SPARES

PART NUMBER	DESCRIPTION	PRICE
GFH3578-3/8-RF	Replacement 100 Micron Stainless Steel Element	£8.75
M503-BRACKET	Wall Support Bracket for Filter	£4.25
GFH3578-3/8- GASKET	Replacement O-Ring	£1.55
MF1006-CM-B	3/8" (10mm) Compression Fittings	£2.50
M5020	PTFE Joining Tape	£0.50

NEED MORE INFO?

Visit us on www.fueldump.co.uk