



## SPECIFICATION SHEET

GOK DEAERATOR

### CONTACT:

01373 822220

sales@fueldump.co.uk

## DESCRIPTION

The GOK De-Aerator is a combination of an oil filter, de-aerator and shut off valve, suitable for kerosene, oil and biofuels with up to 20% fatty acid methyl ester. This de-aerator removes gas/air bubbles from a single line fuel system, helping to eliminate any pump and nozzle problems associated with gas/air in the fluid. This GOK system eliminates multiple external connections, which reduces the risk of leakage, and is suitable for mounting indoors.

**Tip:** This product is not self-priming and a priming pump is required for initial installation.



## FEATURES

- Automatic de-aerator for oil burner
- Maximum operating temperature of 60°C
- Suitable for oil and kerosene
- 3/8" F BSP Inlet/Outlet

PART NUMBER	DESCRIPTION	SPECIFICATIONS	PRICE
GS2000	GOK GS2000 Pro-Fi3 Internal De-Aerator	<ul style="list-style-type: none"> <li>• Nozzle Capacity (l/h) - 80</li> <li>• Oil Flow (l/h) - 200</li> <li>• Max return oil (l/h) - 80</li> <li>• De-aerating capacity (l/h) - 5</li> <li>• Max operating temp - 60°C</li> <li>• Max/Min Pressure - +0.7</li> <li>• Inlet/Outlet - 3/8" F BSP</li> <li>• 70 micron particulate filter</li> </ul>	£138.00

## ACCESSORIES & SPARES

PART NUMBER	DESCRIPTION	SPECIFICATIONS	PRICE
GS2000-KIT	Fitting kit for GOK Deaerator (Internal Installation)	<ul style="list-style-type: none"> <li>• x2 Steel Braided Flexi Oil Lines (1m)</li> <li>• Isolation Valve</li> <li>• Compression Fittings</li> <li>• Nuts &amp; Olives</li> <li>• Copper Pipe Inserts</li> </ul>	£25.00
GS2000-FILT	Spare 50-70 Micron Filter		£4.10
GS2050	Priming Pump for GOK	Complete with 2 Flexible hoses and a variety of screwed adaptors to suit most installations	£84.00

## NEED MORE INFO?

Visit us on [www.fueldump.co.uk](http://www.fueldump.co.uk)