

SPECIFICATION SHEET

PIUSI AUTOMATIC FUEL NOZZLE -ATEX APPROVED

CONTACT:

01373 822220 sales@fueldump.co.uk

DESCRIPTION

The Piusi Automatic ATEX Fuel Nozzles have been specially designed for the safe dispensing of diesel, petrol or kerosene in flammable environments thanks to its ATEX certification. The automatic shut-off mechanism means that these petrol and diesel nozzles stop further fuel from being released out of the spout once the vehicle tank is full, therefore preventing an overflow. These automatic fuel dispensing nozzles are suitable for use with non-resale pumping systems i.e. where private refuelling takes place.

The Automatic 60 ATEX nozzle is commonly used alongside the Piusi EX50 ATEX Pump, and the Automatic 140 ATEX nozzle is for filling large agricultural and plant machinery alongside the Piusi EX140 ATEX Pump.



- · Auto shut off fuel nozzle
- ATEX approved
- Suitable for diesel, petrol & kerosene
- Maximum flow rate: 60ltr Per Min
- Supplied with 1" F BSP Swivel

PART NUMBER	DESCRIPTION	SPECIFICATIONS	PRICE
P8-613020	Piusi Automatic 60 ATEX Fuel Nozzle	 Max flow (lpm) - 60 Inlet - 1" F BSP swivel Spout OD (mm) - 20 Loss of pressure - 0.6 bar @ 60lpm Working pressure - 3.5 bar Test pressure - 5.25 bar Automatic Petrol, kerosene and diesel 	£96.50
P8-F22675000	Piusi Automatic 140 ATEX Fuel Nozzle	 Max flow (lpm) – 1040 Inlet - 1" F BSP swivel Spout OD (mm) - 29 Loss of pressure - 1.5 bar @ 140lpm Working pressure - 3.5 bar Test pressure - 5.25 bar Automatic Petrol, kerosene and diesel 	£155.84