



SPECIFICATION SHEET

PIUSI K24 ADBLUE FLOW METER

CONTACT:

01373 822220

sales@fueldump.co.uk

DESCRIPTION

The Piusi K24 AdBlue™ Flow Meter is a reliable and accurate turbine digital flow meter designed to measure the quantity of AdBlue™, water, windscreen fluid or cattle milk (not for human consumption). This AdBlue™ meter is a lightweight, compact solution that can be fitted inline or at the end of the delivery nozzle for the easiest possible reading, and benefits from a rotatable face for flexible installation.



FEATURES

- Digital turbine AdBlue™ flow meter
- Face can be rotated 4 ways for easy reading
- 1" M BSP Inlet/Outlet c/w socket
- Accuracy +/-1% after calibration
- 5 digit partial and 6 digit totaliser
- Flow rate: 6-100ltrs Per Min
- Flow rate indication
- LCD electronic display (2 x AAA batteries)
- Working temperature -10°C/+50°C
- Suitable for AdBlue™, water & windscreen

PART NUMBER	DESCRIPTION	SPECIFICATIONS	PRICE
P8-F0040710A	Piusi K24 AdBlue™ Flow Meter	<ul style="list-style-type: none">• Max Flow (lpm) - 100• Pressure (bar)-(psi) 10-145• Fluid Viscosity: 2-5.35 cSt• Max Fluid Temperature - +50°C• 1" M BSP c/w socket• 5 digit partial totaliser, 6 digit totaliser	£126.20

NEED MORE INFO?

Visit us on www.fueldump.co.uk