

PRODUCT SPECIFICATION SHEET

Piusi Cube 70 MC Fuel Management System

BRAND:





FLOW RATE:

Product Description

Cube MC is a diesel dispenser specifically for non-commercial use. The uniqueness of this diesel dispenser is its versatility, which makes it suitable for different applications. In fact, it is possible to apply CUBE MC directly on tanks, on the wall, on cisterns, on drums or apply it on its special pedestal.

Another peculiarity of this diesel dispenser is its versatility in being able to adapt to different sectors: agriculture, automotive, logistics, construction and industrial sectors.

The Cube MC fuel dispenser is equipped with a self-priming vane pump with bypass that ensures high performance. The CUBE MC Diesel dispenser is installed on antivibration mounts for better comfort and practicality in use, while the mechanical seal



and the thermal protection against overheating of the induction motor make the product reliable and safe. The nozzle supplied is automatic with a swivel connection and the nozzle holder has a pump start/stop lever. The installation of the mesh filter on the suction side ensures a long life of the pump, because no foreign matter ends up in the rotor, causing a blockage and consequent breakage.

The Cube MC Diesel dispenser is equipped with oval gear flow meter and an electronic control unit for the management of multi-user dispensing operations. The local memory collects the last 255 dispensing operations and thanks to the PC interface, it is possible to export and organize the data. For total control over the use of the fuel dispenser, you can enter the vehicle code, mileage, date and time of dispensing. In addition, the magnetic keys (iButton keys) allow the identification of users for a total tracking of consumption.

Features

- Multi-user management
- O All-in-one equipment
- O Compatible with SSM 2018 software

- O Controls up to 50 120 users (depending on model)
- O Pump start/stop & pre-set dispense features
- Available in 12v/24v/230v

Part Number	Description	Specifications
P8-59400B	Piusi Cube 70MC Fuel Management Unit 230v 50 User	Max flow - 70lpm Voltage - 230v Users - 50 Pump - Panther 72 Nozzle - Auto 60 Flow Meter - K600 Connection - 1" F BSP Flanged Inlet
P8-59415A	Piusi Cube 70MC Fuel Management Unit 230v 120 User	Max flow - 70lpm Voltage - 230v Users - 120 Pump - Panther 72 Nozzle - Auto 60 Flow Meter - K600 Connection - 1" F BSP Flanged Inlet

NEED MORE INFORMATION?

0 01373 822220

sales@fueldump.co.uk

www.fueldump.co.uk

Part Number	Description	Specifications
P8-59413A	Piusi Cube 70MC Fuel Management Unit 12v 50 User	Max flow - 56lpm Voltage - 12v Users - 50 Pump - Panther 72 Nozzle - Auto 60 Flow Meter - K600 Connection - 1" F BSP Inlet
P8-59414A	Piusi Cube 70MC Fuel Management Unit 24v 50 User	Max flow - 70lpm Voltage - 24v Users - 50 Pump - Panther 72 Nozzle - Auto 60 Flow Meter - K600 Connection - 1" F BSP Inlet