




PRODUCT SPECIFICATION SHEET

Piusi K150 ATEX Fuel Flow Meter

BRAND:



SUITABLE FOR:



FLOW RATE:

150_LPM

Product Description

K150 ATEX is expressly engineered to meet the market requirements of a meter suitable for flow rates superior than 120 l/min and that can be used both for fluids such as diesel and biodiesel, as well as in potentially explosives atmosphere; with gasoline for example. K150 is easy to calibrate and ready to use; its aluminium cover and sturdy body make this meter suitable for a wide arrange of application while guaranteeing the same precision and quality that have always featured PIUSI equipment.

The mechanical display allows to read quickly the quantity dispensed. It can be installed everywhere thanks to the (optional) 1,5" flange kit. K150 is certified CE, ATEX/UL and tested in PIUSI laboratories for over 4 milion litres to guarantee the maximum reliability.



Features

- Accuracy +/-1% after calibration
- Working temp -30°C/+60°C
- Suitable for diesel
- Flow rate - 25-150lpm
- 1" F x F BSP Inlet/Outlet
- Easy to install and calibrate

Part Number	Description	Specifications
P8-555B00	Piusi K150 ATEX Fuel Flow Meter	Flow rate - 150lpm Connection - 1" BSPF Pressure - 3.5 PSI / 51 Bar

NEED MORE INFORMATION?

○ 01373 822220

○ sales@fueldump.co.uk

○ www.fueldump.co.uk