

## Product Information

### Specifications

<b>Dimensions: (approx.)</b>	H-105mm x D-(body) 85mm x (foot-print) 116mm to leg extension)
<b>Weight: (approx.)</b>	1kg
<b>Max Negative Head</b>	Factory set at 1.6 meters (max 5m on request)
<b>Max Flow:</b>	25 litres per hour
<b>Max Vacuum:</b>	-0.6 bar / -8.7 PSI
<b>Tank Fitting:</b>	3 leg self tapping/drilling screws & gasket (threaded 1" BSP w/ flange nut available on request)
<b>Outlet Fitting:</b>	1/4" BSP parallel female c/w 10mm hydraulic pushfit as standard
<b>Suitable For:</b>	Diesel, kerosene including blends upto B20/E15
<b>Country of Origin:</b>	England, UK - EC design reg number: 000472493-0001



## Features

- Floating Suction Tube (1.6M)
- Non Return Valve
- 50 Micron Filter
- Diaphragm Anti-siphon Valve
- Anti-spill Valve
- Tank Inlet Fitting 1" BSPM
- Purging / Priming Button
- Surface Gasket
- Waterproof

## Part Numbers

PART NUMBER	DESCRIPTION
<b>TTV-01-C</b>	Tank Top Off Take Valve - For Plastic Tanks
<b>TTV-01</b>	Tank Top Off Take Valve - For Steel Tanks
<b>TTV-01-C-STRP</b>	Tank Top Off Take Valve - For Steel Tanks with Rigid Pipe Fitment

### SPARES AND ACCESSORIES:

<b>TTV-FILTER</b>	Replacement Filter Kit - Includes Filter and Viton O'rings
<b>TTV-ASMODULE</b>	Replacement Anti-Siphon Module
<b>TTV-WEATHER</b>	Weatherproof/Dust Cover Kit Weatherproof/Dust Cover Kit
<b>TTV-FLOAT</b>	Replacement Hose Kit - Includes 2m Suction Hose & Float

Important Note: The pressure is pre-set in the factory at a 1.5m negative head and this is not adjustable by the user (suitable for all known boilers on the market). If you require this to be pre-set to any other pressure between 0-5.5m negative head on request.